



ENERGY

Climate 3000i

CL3000I-SET 70 WE

7733701738

7733701571 / 7733701570



BOSCH

SEER



A+++

A++

A+

A

B

C

D

A++

kW 7,0

SEER 6,4

kWh/annum 383

SCOP



A+++

A++

A+

A

B

C

D

A+++

A+

kW 5,3

SCOP 5,1

kWh/annum 1455

4,9 X

4,0 X

1715 X



62 dB



67 dB





ENERGY

Climate 3000i

CL3000I-SET 70 WE

7733701738

7733701571 / 7733701570



BOSCH

SEER



A+++

A++

A+

A

B

C

D

A++

kW 7,0

SEER 6,4

kWh/annum 383

SCOP



A+++

A++

A+

A

B

C

D

A+++

A+

kW 5,3

SCOP 5,1

kWh/annum 1455

4,9 X

4,0 X

1715 X



62 dB



67 dB



Climate 3000i

CL3000I-SET 70 WE

7733701738

To the extent applicable to the product, the following data are based on the requirements of Regulations (EU) 206/2012 and (EU) 626/2011.

| Productdata | Symbol | Unit | 7733701738 |
|--|----------------------|------|------------|
| model identifier of the indoor elements of the air conditioner | | | 7733701570 |
| model identifier of the outdoor element of the air conditioner | | | 7733701571 |
| Indoor sound power level in cooling mode | L _{WA} | dB | 62 |
| Sound power level outdoors in cooling mode | L _{WA} | dB | 67 |
| Indoor sound power level in heating mode | L _{WA} | dB | 62 |
| Sound power level outdoors in heating mode | L _{WA} | dB | 67 |
| Refrigerant type | | | R32 |
| Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675 kgCO ₂ eq. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO ₂ , over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional. | | | |
| Seasonal energy efficiency ratio | SEER | | 6,4 |
| Efficiency class cooling | | | A++ |
| Energy consumption 383 kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located. | | | |
| Design load P _{designc} | P _{designc} | kW | 7,0 |
| SCOP/A average climate | SCOP/A | | 4,0 |
| Efficiency class heating average climate | | | A+ |
| Energy consumption 1715 kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located. | | | |
| Heating season average | | | Yes |
| Heating season warmer | | | Yes |
| Heating season colder | | | No |
| Design load average climate | P _{designh} | kW | 4,9 |
| Declared capacity at reference design conditions | | kW | 4,0 |
| Back up heating capacity at reference design conditions | | kW | 0,9 |
| Cooling | | | Yes |
| Heating | | | Yes |
| Heating season average | | | Yes |
| Declared capacity for cooling at indoor 27(19) °C and outdoor 35 °C | P _{dc} | kW | 7,0 |
| Declared capacity for cooling at indoor 27(19) °C and outdoor 30 °C | P _{dc} | kW | 5,0 |
| Declared capacity for cooling at indoor 27(19) °C and outdoor 25 °C | P _{dc} | kW | 3,2 |
| Declared capacity for cooling at indoor 27(19) °C and outdoor 20 °C | P _{dc} | kW | 2,1 |
| Declared energy efficiency ratio at indoor 27(19) °C and outdoor 35 °C | EER _d | | 2,8 |
| Declared energy efficiency ratio at indoor 27(19) °C and outdoor 30 °C | EER _d | | 4,5 |
| Declared energy efficiency ratio at indoor 27(19) °C and outdoor 25 °C | EER _d | | 7,5 |
| Declared energy efficiency ratio at indoor 27(19) °C and outdoor 20 °C | EER _d | | 13,1 |
| Declared capacity for heating (average season) at indoor 20 °C outdoor -7 °C | P _{dh} | kW | 4,3 |
| Declared capacity for heating (average season) at indoor 20 °C outdoor 2 °C | P _{dh} | kW | 2,7 |
| Declared capacity for heating (average season) at indoor 20 °C outdoor 7 °C | P _{dh} | kW | 1,8 |
| Declared capacity for heating (average season) at indoor 20 °C outdoor 12 °C | P _{dh} | kW | 2,2 |
| Declared capacity for heating (average season) at indoor 20 °C outdoor bivalent temperature | P _{dh} | kW | 4,3 |
| Declared capacity for heating (average season) at indoor 20 °C outdoor operating limit | P _{dh} | kW | 4,0 |
| Declared coefficient of performance (average season) at indoor 20 °C outdoor -7 °C | COP _d | | 2,8 |

Data at the time of printing. Latest version available on the Internet.

Climate 3000i

CL3000I-SET 70 WE

7733701738

| Productdata | Symbol | Unit | 7733701738 |
|---|------------------|-------------------|------------|
| Declared coefficient of performance (average season) at indoor 20 °C outdoor 2 °C | COPd | | 4,0 |
| Declared coefficient of performance (average season) at indoor 20 °C outdoor 7 °C | COPd | | 4,9 |
| Declared coefficient of performance (average season) at indoor 20 °C outdoor 12 °C | COPd | | 6,2 |
| Declared coefficient of performance (average season) at indoor 20 °C outdoor bivalent temperature | COPd | | 2,8 |
| Declared coefficient of performance (average season) at indoor 20 °C outdoor operating limit | COPd | | 2,7 |
| Bivalent temperature heating - average | Tbiv | °C | -7 |
| Operational limit temperature heating - average | Tol | °C | -15 |
| Cycling interval capacity for cooling | Pcycc | kW | - |
| Cycling interval capacity for heating | Pcych | kW | - |
| Degradation co-efficient cooling | Cdc | | 0,3 |
| Cycling interval efficiency for cooling | EERcyc | | - |
| Cycling interval efficiency for heating | COPcyc | | - |
| Degradation co-efficient heating | Cdh | | 0,3 |
| Electric power modes other than active mode: off mode | P _{OFF} | kW | 0,0 |
| Electric power modes other than active mode: standby mode | P _{SB} | kW | 0,0 |
| Electric power modes other than active mode: thermostat-off mode | P _{TO} | kW | 0,0 |
| Electric power modes other than active mode: crankcase heater mode | P _{CK} | kW | 0,0 |
| Capacity control: fixed | | | No |
| Capacity control: staged | | | No |
| Capacity control: variable | | | Yes |
| Rated air flow indoor | | m ³ /h | 1090 |
| Rated air flow outdoor | | m ³ /h | 3500 |